

SAFETY DATA SHEET

1. Identification

Material name: WATCHDOG H3 WATERPROOFING 330 GAL TOTE
Material: TBS382E

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Barrier Solutions
6402 E. MAIN STREET
REYNOLDSBURG OH 43068
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral	1.22 %
Acute toxicity, dermal	2.02 %
Acute toxicity, inhalation, vapor	70.08 %
Acute toxicity, inhalation, dust or mist	66.29 %

Environmental Hazards

Acute hazards to the aquatic environment Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	97.73 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	50 - <100%
Petroleum distillates	64742-47-8	1 - <5%
Aliphatic naphtha	64742-88-7	1 - <5%
Trade Secret	Trade Secret	1 - <5%
Amorphous silica	7631-86-9	1 - <5%
Carbon Black	1333-86-4	0.1 - <1%
Heavy paraffinic distillate	64741-88-4	0.1 - <1%
Sodium hydroxide	1310-73-2	0.1 - <1%
Hydrogen sulfide	7783-06-4	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Petroleum distillates	TWA	200 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Petroleum distillates	PEL	100 ppm 400 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m ³	US. ACGIH Threshold Limit Values (03 2014)
Aliphatic naphtha	PEL	100 ppm 400 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (01 2017)
Trade Secret - Inhalable fraction. - as allergenic protein	TWA	0.0001 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Heavy paraffinic distillate	PEL	500 ppm 2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Sodium hydroxide	Ceiling	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	2 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrogen sulfide	TWA	1 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	5 ppm	US. ACGIH Threshold Limit Values (2011)
	Ceiling	20 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	50 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation. 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aliphatic naphtha	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Trade Secret - Inhalable - total proteins	TWA	0.001 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Trade Secret - Inhalable fraction. - as allergenic protein	TWA	0.0001 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Québec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Québec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Sodium hydroxide	CEILING	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Sodium hydroxide	CEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Sodium hydroxide	CEILING	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor -

			Regulation Respecting the Quality of the Work Environment) (12 2008)
Aromatic petroleum distillates	TWA	400 ppm 1,590 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Ammonium hydroxide	STEL	35 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ammonium hydroxide	TWA	25 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	35 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Nonane	TWA	200 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nonane	TWA	200 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Nonane	TWA	200 ppm 1,050 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada, Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrogen sulfide	CEILING	10 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Hydrogen sulfide	STEL	15 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	10 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrogen sulfide	TWA	10 ppm 14 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	15 ppm 21 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zinc oxide - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Fume.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12-2008)
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Naphthalene	STEL	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Naphthalene	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	15 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Naphthalene	TWA	10 ppm	52 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	15 ppm	79 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Styrene	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Styrene	TWA	35 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Styrene	TWA	50 ppm 213 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	100 ppm 426 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethyl Acrylate	TWA	5 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	15 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethyl Acrylate	TWA	5 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	15 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethyl Acrylate	TWA	5 ppm 20 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	15 ppm 61 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	10 mg/m3	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	10 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3-Butadiene	TWA	2 ppm	Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3-Butadiene	TWA	2 ppm	Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3-Butadiene	TWA	2 ppm 4.4 mg/m3	Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection:**Hand Protection:** Use suitable protective gloves if risk of skin contact.**Other:** Wear suitable protective clothing.**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.**9. Physical and chemical properties****Appearance****Physical state:** liquid**Form:** liquid**Color:** Dark brown**Odor:** Slight odor**Odor threshold:** No data available.**pH:** No data available.**Melting point/freezing point:** No data available.**Initial boiling point and boiling range:** No data available.**Flash Point:** > 100 °C > 212 °F**Evaporation rate:** Slower than Ether**Flammability (solid, gas):** No**Upper/lower limit on flammability or explosive limits****Flammability limit - upper (%):** No data available.**Flammability limit - lower (%):** No data available.**Explosive limit - upper (%):** No data available.**Explosive limit - lower (%):** No data available.**Vapor pressure:** No data available.**Vapor density:** Vapors are heavier than air and may travel along the floor and in the bottom of containers.**Relative density:** 1.01**Solubility(ies)****Solubility in water:** Dispersible**Solubility (other):** No data available.**Partition coefficient (n-octanol/water):** No data available.**Auto-ignition temperature:** No data available.**Decomposition temperature:** No data available.**Viscosity:** No data available.**10. Stability and reactivity****Reactivity:** No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt	LD 50 (Rat): > 5,000 mg/kg
Petroleum distillates	LD 50 (Rat): > 5,000 mg/kg
Aliphatic naphtha	LD 50 (Rat): > 5,000 mg/kg
Trade Secret	LD 50 (Rat): 5,001 mg/kg

Amorphous silica LD₅₀ (Rat): > 5,000 mg/kg

Carbon Black LD₅₀ (Rat): > 8,000 mg/kg

Heavy paraffinic distillate LD₅₀ (Rat): > 5,000 mg/kg

Sodium hydroxide LD₅₀ (Rabbit): 325 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt LD₅₀ (Rabbit): > 2,000 mg/kg

Petroleum distillates LD₅₀ (Rabbit): > 2,000 mg/kg

Aliphatic naphtha LD₅₀ (Rabbit): > 2,000 mg/kg

Trade Secret LD₅₀ (Rabbit): 5,001 mg/kg

Amorphous silica LD₅₀ (Rabbit): > 2,000 mg/kg

Heavy paraffinic distillate LD₅₀ (Rabbit): > 2,000 mg/kg

Inhalation

Product: ATEmix: 80.29 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Asphalt	in vivo (Rabbit): Not irritant Experimental result, Key study
Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Aliphatic naphtha	in vivo (Rabbit): Irritating Experimental result, Key study
Amorphous silica	in vivo (Rabbit): Not irritant Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Heavy paraffinic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Sodium hydroxide	in vivo (Rabbit): Irritating Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Asphalt	Rabbit, 24 hrs: Not irritating
Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Aliphatic naphtha	Rabbit, 24 - 72 hrs: Not irritating
Amorphous silica	Rabbit, 24 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Heavy paraffinic distillate	Rabbit, 24 hrs: Not irritating
Sodium hydroxide	Rabbit, 1 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Heavy paraffinic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Heavy paraffinic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Petroleum distillates	LC 50 (Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>), 96 h): 2.9 mg/l Mortality
Sodium hydroxide	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): 125 mg/l Mortality
Hydrogen sulfide	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 0.013 - 0.0172 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Sodium hydroxide	EC 50 (Water flea (<i>Ceriodaphnia dubia</i>), 48 h): 34.59 - 47.13 mg/l Intoxication
Hydrogen sulfide	LC 50 (Sand shrimp (<i>Metapenaeus monoceros</i>), 96 h): 0.0352 mg/l Mortality EC 50 (Oligochaete (<i>Stylaria lacustris</i>)): +/- +/- 50 mg/l Intoxication EC 50 (Leech (<i>Herpobdella octoculata</i>)): +/- +/- 10 mg/l Intoxication EC 50 (Oligochaete (<i>Stylaria lacustris</i>)): +/- +/- 10 mg/l Intoxication EC 50 (Tubificid worm (<i>Tubifex tubifex</i>)): +/- +/- 50 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Asphalt	NOAEL (<i>Oncorhynchus mykiss</i> , 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (<i>Oncorhynchus mykiss</i> , 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Aliphatic naphtha	NOAEL (<i>Oncorhynchus mykiss</i> , 28 d): 0.098 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product:	No data available.
-----------------	--------------------

Toxicity to Aquatic Plants

Product:	No data available.
-----------------	--------------------

Persistence and Degradability

Biodegradation

Product:	No data available.
-----------------	--------------------

BOD/COD Ratio

Product:	No data available.
-----------------	--------------------

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye
1,3-Butadiene	Flammability Cancer respiratory tract irritation Central nervous system Eye irritation

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Sodium hydroxide	1000 lbs.
Xylene	100 lbs.
Ammonium hydroxide	1000 lbs.
Nonane	100 lbs.
Hydrogen sulfide	100 lbs.
Propylbenzene	100 lbs.
Cumene	5000 lbs.
Toluene	1000 lbs.
Ethylbenzene	1000 lbs.
Naphthalene	100 lbs.
Benzene	10 lbs.
Styrene	1000 lbs.
Ethyl Acrylate	1000 lbs.
1,3-Butadiene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Delayed (Chronic) Health Hazard
- Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Hydrogen sulfide	100 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Sodium hydroxide	1000 lbs.
Xylene	100 lbs.
Ammonium hydroxide	1000 lbs.
Nonane	100 lbs.
Hydrogen sulfide	100 lbs.
Propylbenzene	100 lbs.
Zinc oxide	
Cumene	5000 lbs.
Toluene	1000 lbs.
Ethylbenzene	1000 lbs.
Naphthalene	100 lbs.
Benzene	10 lbs.
Styrene	1000 lbs.
Ethyl Acrylate	1000 lbs.
1,3-Butadiene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Hydrogen sulfide	500lbs
Asphalt	10000 lbs
Petroleum distillates	10000 lbs
Aliphatic naphtha	10000 lbs
Trade Secret	10000 lbs
Amorphous silica	10000 lbs
Carbon Black	10000 lbs
Heavy paraffinic distillate	10000 lbs
Sodium hydroxide	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Hydrogen sulfide	lbs
1,3-Butadiene	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Asphalt	Carcinogenic. 09 2011
Carbon Black	Carcinogenic. 09 2011
Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011
Cumene	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Ethylbenzene	Carcinogenic. 09 2011
Naphthalene	Carcinogenic. 09 2011

Benzene	Carcinogenic. 09 2011
Benzene	Developmental toxin. 09 2011
Benzene	Male reproductive toxin. 09 2011
Styrene	Carcinogenic.
Styrene	Carcinogenic. 04 2016
Ethyl Acrylate	Carcinogenic. 09 2011
1,3-Butadiene	Carcinogenic. 09 2011
1,3-Butadiene	Developmental toxin. 09 2011
1,3-Butadiene	Male reproductive toxin. 09 2011
1,3-Butadiene	Female reproductive toxin. 09 2011

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Asphalt
Petroleum distillates
Aliphatic naphtha
Amorphous silica
Carbon Black
Heavy paraffinic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Asphalt
Petroleum distillates
Aliphatic naphtha
Amorphous silica
Hydrogen sulfide
Crystalline Silica (Quartz)/ Silica Sand
Benzene
Styrene
Ethyl Acrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Asphalt
Petroleum distillates
Aliphatic naphtha
Amorphous silica

US. Rhode Island RTK

Chemical Identity

Asphalt
Petroleum distillates
Aliphatic naphtha

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol
not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 60 g/l

VOC Method 310 : 4.13 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 02/14/2018

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

